

Data sheet

BLF 130AS

Backlightfilm „frontprint“

Product description:

Transparent premium quality display film. Front side special coated for water resistant prints with highest color brilliance. Suitable for pigmented and dye inks.

Specific feature:

BLF 130AS is an asymmetrically coated, one side matte, transparent polyester film for fastidious applications of graphic arts on inkjet plotters and printers. The glossy backside has an anti-static finish. The material was designed as front print film for picture presentations in light boxes. When printing with pigmented inks BLF 130AS can also be used in areas with high humidity and condensed water. Because the inkjet-coating and the prints are water-resistant, the printed side shows to the viewer (frontprint).

Processing:

For quality reasons the processing and storage of BLF 130 AS „frontadhesive“ should take place in a climate from 35 to 65% relative humidity and at a temperature from 10-30°C. Keep in the original packaging - cardboard box and PE bag. Avoid touching the inkjet coating (wear cotton gloves). In order to achieve optimum printing results BLF 130AS has to be calibrated beforehand to the used printer and the corresponding ink.

Technical specification:

Material:	FOLIE
Application Area:	WEITER VERARBEITET IM AUßENB
Surface:	MATT
Specific gravity:	165,00g/m ²
Thickness:	140,00µm
B1-cert.:	nein
Cold lamination:	ja
Heat lamination:	ja
can be eyeletted:	ja
water resistant:	ja
scratch resistant:	ja
ph-value:	5-6 -log(H ⁺)
Transparenz:	1,7

Data sheet

BLF 130AS

Backlightfilm „frontprint“

[Link zu den Kompatibilitätslisten](#)

Compatibility:

Epson Stylus PRO 9880	exzellent
HP DesignJet 2500CP Dye	ungeeignet
HP DesignJet 5000 UV 42"	sehr gut

Sollten hier keine Daten angezeigt werden oder Sie benötigen ausführlichere Informationen, dann besuchen Sie bitte unsere Internetseiten unter <http://www.rauch-papiere.de/produkte/inkjetmedien.htm> und die damit verbundenen Kompatibilitätslisten.