

Data sheet

Canvas Como PRO

Genuine canvas-linen, mat, Oeko-Tex®

Product description:

Semi-fine, textured canvas, for art reproductions and prestigious picture prints, in tear-resistant 2:1 weave. Certified according to the Oeko-Tex® Standard and highly flame-resistant, in accordance with the new DIN EN 13501-1, very good colour space.

Specific feature:

Canvas Como PRO is a naturally white blended fabric of cotton and polyester fibres, coated for printing with water-based inkjet printing. The coating is fast-drying even at high levels of ink application. The prints impress with high colour brilliance, perfect ink absorption and after drying is complete, they are resistant to water splashes, long-lasting and non-sensitive. Canvas Como PRO stands out through its extremely good flatness qualities both when printed and unprinted, particularly also after the application of a protective paint such as our ClearShield FineArt paint, which was specially developed for use on canvases. Pictures printed on Canvas Como PRO with pigment-based inks are to a large extent resistant to the effects of light, making it very suitable for archiving purposes. The Canvas fabric is certified as highly flame-resistant in accordance with the new European DIN EN 13501-1 (comp. B1) Canvas Como PRO fulfils completely the applicable human-ecological requirements in accordance with Oeko-Tex® Standard 12.0.09048.

Processing:

For quality reasons, the processing and storage of Canvas Como PRO should take place in a climate of 35-65% relative humidity and at a temperature of 10-30°C. Store in the original packaging in a cool, dry place, clean and dust free. A 24-hour climate adaptation in the processing area is recommended. Attention: turn off the automatic cutting option on your printer! We recommend you feed approximately 50cm of the media out before printing and cut manually after printing.

Technical specification:

Material:	GEWEBE
Application Area:	NUR IM INNENBEREICH
Surface:	MATT
Specific gravity:	340,00g/m ²
Thickness:	400,00µm
B1-cert.:	ja
Cold lamination:	nein
can be sewn:	ja
can be stretched:	ja
water resistant:	ja
scratch resistant:	ja
Color L:	94,8
Color a:	-0,0
Color b:	1,0
UV-whiteness:	>90
ph-value:	6,0
schwer entflammbar:	DIN EN 13501-1
Oeko-Tex Standard 100:	12.0.09048
DIN ISO 16245	Nein

This information consists of standard values for your guidance. Before using our print media, please check their suitability to your printer and for your intended application. Taking account of technical development, product specifications may be amended without prior notice at any time. There is no guarantee that the same results can be achieved. We can not accept liability for any errors resulting from technical changes in printers and / or inks.