

# Data sheet

## PRC 120SK

Inkjet paper, matte, self-adhesive

### Product description:

Coated mat paper, for presentation prints with high resolution. Brilliant color reproduction due to a special color receipt coat. Self-adhesive Backside cover: about 60g/m<sup>2</sup> Printing side: paper 120g/m<sup>2</sup>

### Specific feature:

The mat coated, neutral white surface of PRC 120 sk is homogeneously satinated and has a special color receiving coat. Therefore this special paper is recommended for the output of high-quality presentation plots with high resolution. This product is suitable for the application on most of the common color inkjet plotters with dye-based and pigmented inks. PRC 120 sk is an inkjet paper, which convinces by intensive colors, selective and precise reproduction of color surfaces, shape and outline, at a short drying time. The backside is provided with a pressure-sensitive, permanent adhesive on the basis of a water-soluble acrylate and sticks on all common clean and smooth backgrounds. The adhesive layer is covered with a film liner .

### Processing:

For quality reasons, it must be handled and stored in atmospheres with approx. 50% relative humidity and at a temperature of 23°C in the original packaging in a cool, dry, clean and dust-free environment. We recommend that it is held for 24 hours before use, in the location where it is going to be used, to allow it to adapt to the climate. Avoid touching the inkjet layer. Wear cotton gloves. Please remove the roll out of the printer overnight to avoid liner delamination.

### Technical specification:

Material:	PAPIER
Application Area:	NUR IM INNENBEREICH
Specific gravity:	120,00g/m <sup>2</sup>
Specific gravity carrier:	60,00g/m <sup>2</sup>
Specific gravity complete:	180,00g/m <sup>2</sup>
Thickness:	130,00µm
Thickness Carrier:	70,00µm
B1-cert.:	nein
Cold lamination:	ja
Color L:	96,8
Color a:	1,8
Color b:	-7,55
Whiteness (R457):	> 93
Klebekraft (auf Stahl):	6N/25mm (Prüfwinkel 180°)
DIN ISO 16245	Nein
FSC®	IMO-COC-150296, FSC Mix Credit

This information consists of standard values for your guidance. Before using our print media, please check their suitability to your printer and for your intended application. Taking account of technical development, product specifications may be amended without prior notice at any time. There is no guarantee that the same results can be achieved. We not accept liability for any errors resulting from technical changes in printers and / or inks



Das Zeichen für verantwortungsvolle  
Waldwirtschaft  
FSC® C127156