

Data sheet

signJET Display & Sticker 190

Satin PP-Display-Film, self adhesive

Product description:

White satin tear resistant polypropylene film with water resistant coating for solvent and eco-solvent inks. Selfadhesive glue for easy application and remove. Features high stability, print sharpness and colour brilliance.

Specific feature:

signJET Display & Sticker 190 is a satin coated and tear-resistant Polypropylene-film with a waterfast coating for solvent inks. The Product has a paper-like touch. The printouts are characterised by high color brilliance, high image definition and perfect flatness. Special solvent coating allows very good water resistancy when printed with Eco-Sol-, or Solvent inks The film has very good lamination characteristics (cold-/and hot laminates). The special solvent coating allows to combine the ecological and physical characteristics of a polypropylene film with the advantages of very durable inks. signJET Display & Sticker 190 is suitable very good for easy tack stickers, sign and dadvertising displays, is both indoor and outdoor usable.

Processing:

For quality reasons, it must be handled and stored in atmospheres with approx. 50% relative humidity and at a temperature of 23°C in the original packaging in a cool, dry, clean and dust-free environment. We recommend that it is held for 24 hours before use, in the location where it is going to be used, to allow it to adapt to the climate. Avoid touching the inkje layer. Wear cotton gloves. Please remove the roll out ofthe printer overnight to avoid liner delamination.

Technical specification:

| | |
|----------------------------|------------------------|
| Material: | FOLIE |
| Surface: | SEIDENMATT |
| Specific gravity: | 150,00g/m ² |
| Specific gravity carrier: | 140,00g/m ² |
| Specific gravity complete: | 290,00g/m ² |
| Thickness: | 190,00µm |
| Thickness Carrier: | 135,00µm |
| B1-cert.: | nein |
| Cold lamination: | ja |
| Heat lamination: | ja |
| can be eyeletted: | ja |
| can be stretched: | ja |
| water resistant: | ja |
| scratch resistant: | ja |
| Opacity: | 90% |
| Klebekraft auf Glas: | 0,5 N/25mm |

This information consists of standard values for your guidance. Before using our print media, please check their suitability to your printer and for your intended application. Taking account of technical development, product specifications may be amended without prior notice at any time. There is no guarantee that the same results can be achieved. We not accept liability for any errors resulting from technical changes in printers and / or inks