

## signJET VF3011

Glossy monomeric vinyl film B1

### Product description:

Glossy white monomeric vinyl film, 4 year working life, grey adhesive is removable leaving no residue, certified fire-retardant according to DIN 4102-B1 on FOREX Classic.

### Specific feature:

VF3011 is a monomeric plasticized, calendered vinyl film with a matt white surface. Prints on VF3011 are characterized by promotionally effective colour effects. The grey pigmented dispersions-acrylate adhesive thoroughly conceals the underlying surfaces and is completely removable. The silicon backliner ensures good flatness during the complete work process.

### Processing:

For quality reasons, it must be handled and stored in atmospheres with approx. 50% relative humidity and at a temperature of 23°C in the original packaging in a cool, dry, clean and dust-free environment. We recommend that it is held for 24 hours before use, in the location where it is going to be used, to allow it to adapt to the climate. Avoid touching the inkjet layer. Wear cotton gloves. Please remove the roll out of the printer overnight to avoid liner delamination.

### Technical specification:

Material:	FOLIE
Application Area:	VOLL AUSSENBEREICHTAUGLICH
Surface:	GLAENZEND
Specific gravity:	95,00g/m <sup>2</sup>
Specific gravity carrier:	135,00g/m <sup>2</sup>
Specific gravity complete:	230,00g/m <sup>2</sup>
Thickness:	100,00µm
Thickness Carrier:	145,00µm
B1-cert.:	ja
Cold lamination:	ja
water resistant:	ja
scratch resistant:	ja
Bruchdehnung längs:	> 130% (DIN EN ISO 527)
Bruchdehnung quer:	> 150% (DIN EN ISO 527)
Zugfestigkeit längs:	> 19 MPa (DIN EN ISO 527)
Zugfestigkeit quer:	> 19 MPa (DIN EN ISO 527)
Klebkraft:	10 N/25mm (FTM 1)
DIN ISO 16245	Nein

This information consists of standard values for your guidance. Before using our print media, please check their suitability to your printer and for your intended application. Taking account of technical development, product specifications may be amended without prior notice at any time. There is no guarantee that the same results can be achieved. We can not accept liability for any errors resulting from technical changes in printers and / or inks.