

Product and description	Data				Prices in €	
					per unit	per m ²
Fabrics/Mesh						
Mesh Pro B1						
PES-Mesh with liner						
White matt polyester mesh for in and outdoor applications. Printable on one side, with film backliner. 1 x 1mm hole size (with bridge).	300g	1.120 mm	30,0 m	1 Rll.	1338120523	177,58 5,29
	54"	1.370 mm	30,0 m	1 Rll.	1338120593	217,21 5,29
		1.600 mm	30,0 m	1 Rll.	1338120633	253,68 5,29
Canvas Catania						
Satin production canvas						
Coated Canvas for high volume professional artist reproduction, satin white Poly-Cotton 2:1 base, very tear resistant due to special material structure. Excellent printability and water resistant drying. Crease free coating and fast drying	390g	36"	914 mm	15 m	1 Rll.	1340012431 186,89 13,63
	3"	42"	1.067 mm	15 m	1 Rll.	1340012511 218,17 13,63
	3"	54"	1.372 mm	15 m	1 Rll.	1340012591 280,53 13,63
	3"	60"	1.524 mm	15 m	1 Rll.	1340012611 311,61 13,63
Canvas Savona FR						
Mat production canvas						
Fine mat coated Canvas for artist reproduction, Poly-Cotton 2:1 base, very tear resistant due to special material structure. Flexible coating, optimized for latex technology, water-resistant,	390g	36"	914 mm	25 m	1 Rll.	1340004432 ↑ 317,60 13,90
		42"	1.067 mm	25 m	1 Rll.	1340004512 ↑ 370,76 13,90
		54"	1.372 mm	25 m	1 Rll.	1340004592 ↑ 476,74 13,90
		60"	1.524 mm	25 m	1 Rll.	1340004612 ↑ 529,56 13,90
			2.100 mm	30 m	1 Rll.	1340004803 ↑ 881,17 13,99
			2.500 mm	30 m	1 Rll.	1340004963 ↑ 1.049,01 13,99
		3.100 mm	30 m	1 Rll.	1340004983 ↑ 1.300,77 13,99	
PopArt Canvas light						
Mat production canvas						
Coated Canvas for high volume professional artist reproduction, satin white Poly-Cotton 2:1 base, very tear resistant due to special material structure. Excellent printability and water resistant drying. Crease free coating and fast drying. RollUp use	280g	44"	1.118 mm	30,5 m	1 Rll.	1340013523 218,18 6,40
		60"	1.524 mm	30,5 m	1 Rll.	1340013613 297,41 6,40
signJET Persenning Heavy POS						
textured grey back blackout fabric						
Lightly structured polyester fabric with matte reflexion-free surface. Tear-resistant scarf fabric for banners, interior decoration, roll-up displays with perfect flatness and with B1 flame resistance. Easy to process with a light-proof grey back for RollUp displays	300g	36"	914 mm	30 m	1 Rll.	1354000433 232,70 8,49
		42"	1.067 mm	30 m	1 Rll.	1354000513 271,65 8,49
		50"	1.270 mm	30 m	1 Rll.	1354000563 323,33 8,49
		60"	1.524 mm	30 m	1 Rll.	1354000613 388,00 8,49

Product and description	Data	Prices in €			
		per unit	per m ²		
Phototex					
Polyester Cellulose Fabric selfadhesive					
<i>Finely structured, self-adhesive textile for brilliant prints with bright, clear colors. Sticks to textiles, furniture, glass, panels, etc. Due to the unique adhesive, PhotoTex is removable residue-free and re-positionable many times over.</i>	250g	42" 1.067 mm 30,5 m	1 Rll. 1356001513	715,09	21,97
		54" 1.370 mm 30,5 m	1 Rll. 1356001593	873,39	20,90
		60" 1.524 mm 30,5 m	1 Rll. 1356001613	970,90	20,89
Phototex BO					
Polyester Cellulose Fabric selfadhesive					
<i>Finely structured, self-adhesive textile for brilliant prints with bright, clear colors. Sticks to textiles, furniture, glass, panels, etc. Due to the unique grey adhesive, PhotoTex BO is removable residue-free and re-positionable many times over.</i>	250g	42" 1.067 mm 30,5 m	1 Rll. 1356101513	756,30	23,24
		54" 1.372 mm 30,5 m	1 Rll. 1356101593	972,81	23,25
		60" 1.524 mm 30,5 m	1 Rll. 1356101613	1.080,66	23,25
Wand Vlies Smooth					
Matt Photo Wall Paper					
<i>This fine structured fleece gives vivid, sharp wallcovering print results with brilliant colors. 100% PVC-free, universal printable and easy to apply, B1 fire retardant when glued on inflammable base.</i>	210g	42" 1.067 mm 50,0 m	1 Rll. 1355600515	450,30	8,44
		60" 1.524 mm 50,0 m	1 Rll. 1355600615	643,17	8,44
Wand Vlies Smooth SK					
Polyester photo fleece self adhesive					
<i>Soft smooth fleece for sharp and brilliant wall coverings and photo wallpapers, selfadhesive. The fleece is 100% PVC-free, universally printable and B1 fireretardant certified when applied to a nonflammable surface</i>	280g	42" 1.060 mm 30,0 m	1 Rll. 1355700513	417,53	13,13